



Model	A1263NL	A1263PL
Signal System	NTSC : 525 Lines	PAL : 525 Lines
Scanning System	2:1 Interlace	
Scanning Frequency(H)	15.734 KHz	15.625kHz
Scanning Frequency(V)	59.94 Hz	50Hz
Image Sensor	1/4 inch SONY Super HAD CCD	
Total Pixels Number	811 (H) x 508 (V) 410K	795(H) x 596(V) 470K
Effective Pixels Number	768 (H) x 494 (V) 380K	752(H) x 582 (V) 440K
Horizontal Resolution	480 TV Lines	
Video Output Level	1.0 Vp-p (75 Ω , Composite)	
S/N Ratio	More than 48dB (AGC Off)	
Digital Zoom Ratio	10x (Total Zoom Ratio: 220x), 2x ~ 10x Variable	
Lens	22x Optical Zoom (F 1.6, f=3.9 ~ 85.8mm) Video AF	
Min. Illumination	0.001 Lux (DSS)	
Camera Control	Rear Button, RS-485 (Pelco-D) / PTZ Controller Interface	
Day&Night Type	Digital Slow Shutter (Off / 2 FLD ~ 128 FLD)	
Focus Mode	Auto / Manual	
OSD	On/Off	
Input/Output Connector	Control: 5 Pin Terminal, Power: 2 Pin Terminal, Video: BNC	
Electronic Shutter Speed	1/60 ~ 1/10,000 sec.	1/50~10,000sec
Supplied Voltage	DC 9V ~ 15V (Recommendation DC12V±0.5V)	
Power Consumption	Max. 5.4W / 450mA	
Dimensions	58(W) x 58(H) x 103.4(D) mm	